


Electrical
 Votag Rating:50V AC(rms)/DC
 Current Rating:0.5A AC(rms)/DC
 Contact Resistance:50 mΩ Max
 Insulation Resistance:100 MΩ min
 Dielectric Withstanding Voltage:200V AC r.m.s
 Operating Temperature:-40°C~+80°C
Materials
 Housing:High Temperature Plastic
 UL 94V-0
 Terminal:Copper Alloy
 Material: PA9T
 Contact:phosphor bronzae:GloPlating

HGH	PLUG	SOCKET
3.0	0.8	2.2
3.5	1.3	2.2
4.0	1.0	3.0
4.5	1.0	3.5
5.0	2.0	3.0
5.5	1.0	4.5
6.0	2.5	3.5
6.5	2.0	4.5

	A	B	C	D	E
8P	4.70	1.50	1.40	2.40	2.00
10P	5.20	2.00	2.90	3.90	2.50
12P	5.70	2.50	3.40	4.40	3.00
14P	6.20	3.00	3.90	4.90	3.50
16P	6.70	3.50	4.40	5.40	4.00
18P	7.20	4.00	4.90	5.90	4.50
20P	7.70	4.50	5.40	6.40	5.00
22P	8.20	5.00	5.90	6.90	5.50
24P	8.70	5.50	6.40	7.40	6.00
26P	9.20	6.00	6.90	7.90	6.50
28P	9.70	6.50	7.40	8.40	7.00
30P	10.2	7.00	7.90	8.90	7.50
32P	10.7	7.50	8.40	9.40	8.00
34P	11.2	8.00	8.90	9.90	8.50
36P	11.7	8.50	9.40	10.40	9.00
38P	12.2	9.00	9.90	10.90	9.50
40P	12.7	9.50	10.40	11.40	10.0
42P	13.2	10.0	10.90	11.90	10.5
44P	13.7	10.5	11.40	12.40	11.0
46P	14.2	11.0	11.90	12.90	11.5
48P	14.7	11.5	12.40	13.40	12.0
50P	15.2	12.0	12.90	13.90	12.5
60P	17.7	14.5	15.50	16.40	15.0
80P	22.7	20.4	20.50	21.40	20.0
100P	27.7	25.4	25.50	26.40	25.0

MICRO BOARD-T0-BOARD PITCH0.5mm (公)

Customer:	Approval:	Unit	Scale	Date
Drawing No:	Check:	mm	5:1	15.03.15



P/NO:	Pin Longger:	Signaturer:
-------	--------------	-------------

深圳市永连旺电子有限公司